

LM750EVGB MYQ DC ROLLING DOOR OPENER

Fast, silent & powerful DC motor with soft start and soft stop.



KEY FEATURES

HEAVY-DUTY

DC motor with automatic force sensing

LIFTING

For doors up to 120 kg

LED LIGHT

LED turns on with activation

MYQ COMPATIBLE



SMART

MYQ MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.

LOW STANDBY SAVES YOUR MONEY.

SPACE-SAVING DESIGN OPENS UP THE CEILING.

SOFT-START AND SOFT-STOP FOR SMOOTH OPERATION.

QUIET AND RELIABLE

QUIET DC MOTOR 59 DB NOISE LEVEL ELIMINATES NOISE AND VIBRATIONS THROUGH THE CEILING AND PROVIDES SMOOTH OPERATION.

HEAVY LIFTING POWER OPERATES DOORS UP TO 120 KG. FOR DOORS UP TO 18m²

WARRANTY MOTOR: 5 YEARS, ACCESSORIES: 2 YEARS.

SECURE & SAFE

AUTOMATIC GARAGE DOOR OPENERS IMPEDE UNAUTHORISED ACCESS TO THE GARAGE.

TIMER-TO-CLOSE² AUTOMATICALLY CLOSES THE DOOR AFTER A PRESET AMOUNT OF TIME.

EVOLUTION RADIO (SECURITY+ 2.0[®]) SENDS A NEW CODE WITH EVERY REMOTE CLICK.

AUTOMATIC FORCE SETTING & OBSTACLE DETECTION.

AUDIBLE SIGNAL (OPTIONAL).

PARTIAL OPENING.

INCLUDED ACCESSORIES:

4-CHANNEL 868 MHz REMOTE CONTROL

Operates up to 4 openers. Compact to provide quick, easy garage access.



TX4EVS

2-BUTTON WIRELESS WALL CONTROL

Operates up to 2 openers. Control your garage door without a remote control.



128EV

POWERFUL ADD-ONS:

INTERNET GATEWAY²

MyQ technology that connects to the internet and allows monitoring and control of the garage door opener.



828EV

WIRELESS KEYPAD

Provides convenient, secure access from outside the garage with a 4-digit PIN, temporary PIN possible.



747EV

FAILSAFE SAFETY SENSOR

2-wire system with LiftMaster signal IP44, range 15 meters.



772E

4-CHANNEL UNIVERSAL REMOTE CONTROL

Operates up to 4 openers. Compact to provide quick, easy garage access.



TX4UNIF

GARAGE DOOR MONITOR²

MyQ enabled technology allows monitoring and closing up to four garage doors from any room in the house.



829EV

FAILSAFE SAFETY SENSOR

2-wire system with LiftMaster signal IP44, range 10 meters.



771EVK

LM750EVGB 550H
MYQ DC ROLLING DOOR OPENER
FOR DOORS UP TO 120 KG

¹In connection with MyQ.

²needs safety sensors.

MASTERFUL ENGINEERING.

MYQ DC DIRECT DRIVE „ROLLING DOOR“
FOR DOORS UP TO 120 KG.

MOTOR



- Heavy-Duty 24 V DC
- Automatic Thermal Protection
- Permanent Lubrication
- Operating Temperature: -25°C to 55°C

POWER



- 220-240 V AC
- 50/60 Hz Voltage
- 0.8 W Stand-by Power
- 175 cm Power Cord UK

MECHANICS



- High Quality Chassis and Cover
- Reliable & Powerful Direct Drive Mechanism
- Automatic Force Setting
- Electronic Limits for Easy Setup
- Maintenance-Free Operation



Minimum distance from
edge of curtain to edge
of door bracket 45 mm

STANDARD SPECS.

SECURE

EVOLUTION RADIO (Security+ 2.0*)



- 4-Button Remote Control (TX4EVS)
- Remote Control: **868 MHz Tri-Band**
- Rolling Door Opener: Frequency Agile on 868, 433.30, 433.92 and 434.54 MHz
- Copy-Protected Coding

SMART

RADIO



- Provides 2-way communication from rolling door opener and accessories.
- Receiver with 64 memory registers.

HOMELINK® COMPATIBLE
(VERSION V OR SOFTWARE REV. 8)¹

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING LED LIGHT



- LED turns on with activation
- Turns off 3 minutes after operation
- 0.8 W Stand-by Power

SAFETY AND SECURITY.

- External Quick Release (optional)
- Down Safety Reverse
- Up Safety Stop
- Soft-Start and Soft-Stop
- Timer to Close (automatic close) Programming (when safety sensors connected)



For more information visit us at liftmaster.eu
or contact your local dealer.



www.hekopeners.nl
info@hekopeners.nl
+31-(0)20-4899.459